

主要产品种类

Main Products Categories

G71 型金属化薄膜电容器/DC-Link/二次滤波 Metalized film capacitor type
G71/ DC-Link/ Secondary filtering application

特点 Characteristics

- | | |
|-----------------|---|
| 1.分割/非分割金属化聚丙烯膜 | segment/no segment metalized polypropylene film |
| 2.低电感 | low self-inductance |
| 3.损耗非常小 | lower loss factor |
| 4.低 ESR | low ESR |
| 5.能承受大电流 | high peak current capability |
| 6.耐高浪涌电流能力 | high surge current capability |
| 7.自愈性 | self healing |
| 8.长寿命 | long life expectancy |
| 9.易于安装 | install conveniently |
| 10.压扁芯子 | Flat winding |

性能指标 Specification

额定电压	Rated voltage	500~6000VDC
额定电容量	Capacitance	100μF~20000μF
容量偏差	Capacitance tolerance	±2.5%，±5%，±10%
介质损耗角正切	Media loss factor	2×10^{-4}
损耗角正切	Loss factor	$\leq 20 \times 10^{-4}$ (1V,100Hz)
端子间耐电压	Test voltage between terminals	1.5U _n , 10/60s
端子与外壳间耐电压	Test voltage between terminals and case	(2U _n +1000)VAC, 60s
运行温度（外壳）	Operating temperature(case)	-40℃~+70℃
热点温度	Hot spot temperature(θ _{HS})	-40℃~+85℃
预期寿命（小时）	Life expectancy(hours)	>100000
气候类别	Climate category	40/85/56
封装	Coating	不锈钢/铝 Stainless steel/Aluminum
填充材料	Filling material	聚氨酯/树脂 Polyurethane/resin
引用标准	Reference standard	IEC61881、IEC61071、GB/T 25121 GB/T 17702

客户需要特殊尺寸，请联系我们。

Please contact us if customers require special sizes.