

Main Products Categories

Y62 型金属化薄膜电容器/DC-Link/二次滤波 Metalized film capacitor type Y62/ DC-Link/ Secondary filtering application

特点 Characteristics

- | | |
|------------------|---|
| 1. 分割/非分割金属化聚丙烯膜 | segment/no segment metalized polypropylene film |
| 2. 低电感 | low self-inductance |
| 3. 损耗非常小 | lower loss factor |
| 4. 低 ESR | low ESR |
| 5. 能承受大电流 | high surge current capability |
| 6. 耐高浪涌电流能力 | high surge current capability |
| 7. 自愈性 | self healing |
| 8. 长寿命 | long life expectancy |
| 9. 易于安装 | install conveniently |
| 10. 圆芯子 | cylindrical wind |

性能指标 Specification

额定电压	Rated voltage	500~6000VDC
额定电容量	Capacitance	100 μ F~16500 μ F
容量偏差	Capacitance tolerance	$\pm 5\%$, $\pm 10\%$
介质损耗角正切	Media loss factor	2×10^{-4}
损耗角正切	Loss factor	$\leq 20 \times 10^{-4} (1V, 100Hz)$
端子间耐电压	Test voltage between terminals	1.5U _n , 10/60s
端子与外壳间耐电压	Test voltage between terminals and case	(2U _n +1000)VAC, 60s
运行温度（外壳）	Operating temperature(case)	-40℃~+70℃
热点温度	Hot spot temperature(θ_{HS})	-40℃~+85℃
预期寿命（小时）	Life expectancy(hours)	> 100000
气候类别	Climate category	40/85/56
封装	Coating	不锈钢 Stainless steel
浸渍剂	Impregnant	植物油 Vegetable oil
引用标准	Reference standard	IEC61881、IEC61071、GB/T 25121 GB/T 17702

客户需要特殊尺寸，请联系我们。

Please contact us if customers require special sizes.